

APPLICATION:	PRODUCT NAME: PRE-RINSE, SWIVEL STYLE, BACKSPASH MOUNT
JOB NAME:	SPECIAL CONFIGURATION <input type="checkbox"/> _____ CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.
<p>36-1/8" [918mm]</p> <p>11-1/2" [292mm]</p> <p>WALL BRACKET</p> <p>12" (MAX) [305mm]</p> <p>6-1/2" [166mm]</p> <p>8" [204mm]</p> <p>4-1/4" [105mm]</p> <p>1-3/8" [34mm]</p> <p>2-3/8" [60mm]</p> <p>1/2" NPT MALE</p> <p>SLIP JOINT</p> <p>ROUGH-IN: Ø7/8" [22mm]</p> <p>8" [204mm]</p>	
MODEL: <input type="checkbox"/> 13439 ULTRA SPRAY VALVE, WALL BRACKET <input type="checkbox"/> 13404 ULTRA SPRAY VALVE, NO WALL BRACKET	
OPTIONS OR MODIFICATIONS: <input type="checkbox"/> SUPPLY LINES (24" OR 36") CIRCLE LENGTH <input type="checkbox"/> ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE <input type="checkbox"/> IN-LINE DUAL CHECK VALVE <input type="checkbox"/> PIPE HOOK <input type="checkbox"/> BRUSH <input type="checkbox"/> ELBOWS <input type="checkbox"/> VANDAL RESISTANT KIT <input type="checkbox"/> HANDLES (CROSS OR WRIST) CIRCLE STYLE <input type="checkbox"/> OTHER _____	
<p>FEATURES</p> <p>CONTROL VALVE</p> <ul style="list-style-type: none"> * 8" BACKSPASH MOUNT * INTERNAL SPRING LOADED CHECK VALVES * SWIVELLING SEAT DISKS * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS <p>HOSE</p> <ul style="list-style-type: none"> * 15-1/2" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3 PLY FIBER REINFORCED INTERNAL RUBBER HOSE * REPAIRABLE IN FIELD WITH SIMPLE TOOLS <p>ULTRA SPRAY VALVE</p> <ul style="list-style-type: none"> * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI * CLEANS FASTER - TEST PROVEN * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK * INTERCHANGEABLE - FITS ALL BRANDS <p>SYSTEM LIMITS</p> <ul style="list-style-type: none"> * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC <p>SHIPPING WEIGHT</p> <ul style="list-style-type: none"> * 12.0 LBS 	
<p>FISHER FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com</p>	
EPAct 2005 Compliant	ANSI/A112.18.1M