

APPLICATION:	
JOB NAME:	
QUANTITY:	ITEM NO.



MODEL	DIM "A"	DIM "B"	DIM "C"
1686	1-3/4"	5-3/8"	6"
	[44.5mm]	[136.5mm]	[152.4mm]
1694	2"	5-7/8"	8"
	[50.8mm]	[149.2mm]	[203.2mm]
1708	2-5/8"	6-3/8"	10"
	[66.7mm]	[161.9mm]	[254.0mm]
1716	3-1/4"	6-7/8"	12"
	[82.6mm]	[174.6mm]	[304.8mm]
1724	3-7/8"	7-3/4"	14"
	[98.4mm]	[196.9mm]	[355.6mm]
1759	4-5/8"	8-3/8"	16"
	[117.5mm]	[212.7mm]	[406.4mm]

ROUGH-IN:



(F) ANSI/A112.18.1M

PRODUCT NAME:

WIDESPREAD DECK FAUCET

SPEC. 1686 REV. B

SPECIAL CONFIGURATION

CHECK BASE MODEL AND OPTIONS

MODEL:

- ☐ 1686 W/ 6" SWING SPOUT
- ☐ 1694 W/ 8" SWING SPOUT
- ☐ 1708 W/ 10" SWING SPOUT
- ☐ 1716 W/ 12" SWING SPOUT
- ☐ 1724 W/ 14" SWING SPOUT
- ☐ 1759 W/ 16" SWING SPOUT

OPTIONS OR MODIFICATIONS:

- $\hfill \square$ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
- ☐ DJ SUB-ASSY (7-1/4" OR 13") CIRCLE LENGTH
- ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
- □ VANDAL RESISTANT KIT
- ☐ OTHER

FEATURES:

- * WIDESPREAD DECK ADJUSTS FROM 6" TO 24"
- * SWIVELLING SEAT DISKS
- * HOT SIDE STEM RIGHT HAND
- * COLD SIDE SEAT LEFT HAND
- * STAINLESS STEEL SEATS
- * STAINLESS STEEL SEAT SCREWS
- * STAINLESS STEEL HANDLE SCREWS

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX.
- * PRESSURE 200 PSI MAX. STATIC
- * 2.20 GPM AT 80 PSI

SHIPPING WEIGHT

* 5.0 LBS

