
H FAUCET	SPEC. FA
RATION EL AND OPTIONS	표- 수
WITH 7" DJ SPOUT WITH 7" DJ SPOUT	DJ-4BSEE

APPLICATION:

JOB NAME:


QUANTITY:

ITEM NO.



MODEL	DIM "A"	DIM "B"
19690	7" [177.8mm]	6" [152.4mm]
19704	7" [177.8mm]	8" [203.2mm]
19712	7" [177.8mm]	10" [254mm]
19720	7" [177.8mm]	12" [304.8mm]
19739	7" [177.8mm]	14" [355.6mm]
19747	7" [177.8mm]	16" [406.4mm]

ROUGH-IN:



(R) ANSI/A112.18.1M

4" C/C BACKSPLASH FAUCET

SPECIAL CONFIGURATION

CHECK BASE MODEL AND OPTION

MODEL:

- □ 19690 W/6" SWING SPOUT WITH 7" DJ SPOUT□ 19704 W/8" SWING SPOUT WITH 7" DJ SPOUT
- ☐ 19712 W/10" SWING SPOUT WITH 7" DJ SPOUT
- ☐ 19720 W/12" SWING SPOUT WITH 7" DJ SPOUT
- ☐ 19739 W/14" SWING SPOUT WITH 7" DJ SPOUT
- ☐ 19747 W/16" SWING SPOUT WITH 7" DJ SPOUT

OPTIONS OR MODIFICATIONS:

- ☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
- DJ SUB-ASSY (7-1/4")OR 13") CIRCLE LENGTH
- **■** ELBOWS
- □ VANDAL RESISTANT KIT
- ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
- □ OTHER _____

FEATURES:

- * 4" C/C BACKSPLASH
- * SWIVELLING SEAT DISKS
- * HOT SIDE STEM RIGHT HAND
- * COLD SIDE STEM LEFT HAND
- * STAINLESS STEEL SEATS
- * STAINLESS STEEL SEAT SCREWS
- * STAINLESS STEEL HANDLE SCREWS
- * 1/2" SLIP JOINT

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 160°F MAX.
- * PRESSURE 200 PSI MAX. STATIC
- * 2.20 GPM AT 80 PSI

SHIPPING WEIGHT

* 4.25 LBS

FISHER MANUFACTURING COMPANY

TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com