

APPLICATION:	
JOB NAME:	
QUANTITY:	ITEM NO.



MODEL	DIM "A"	DIM "B"	DIM "C"
73374	8-3/4"	12-1/2"	5-1/2"
	[222.3mm]	[317.5mm]	[139.7mm]
73375	5"	8-3/4"	3-1/2"
	[127.0mm]	[222.3mm]	[88.9mm]
19852	8-3/4"	12-1/2"	5-1/2"
	[222.3mm]	[317.5mm]	[139.7mm]
19844	5"	8-3/4"	3-1/2"
	[127.0mm]	[222.3mm]	[88.9mm]

ROUGH-IN:



(F) ANSI/A112.18.1M

PRODUCT NAME:

4" C/C BACKSPLASH FAUCET WITH SWIVEL GOOSENECK SPOUT

SPECIAL CONFIGURATION

CHECK BASE MODEL AND OPTIONS

MODEL:

- ☐ 73374 4" C/C BACKSPLASH W/ 12" SGN, 0.35 GPM
- ☐ 73375 4" C/C BACKSPLASH W/ 6" SGN, 0.35 GPM
- ☐ 19852 4" C/C BACKSPLASH W/ 12" SGN, 2.2 GPM
- ☐ 19844 4" C/C BACKSPLASH W/ 6" SGN, 2.2 GPM

OPTIONS OR MODIFICATIONS:

- ☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
- ☐ IN-LINE DUAL CHECK VALVE
- ☐ ELBOWS
- ☐ VANDAL RESISTANT KIT
- ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
- ☐ OTHER

FEATURES:

CONTROL VALVE

- * 4" C/C BACKSPLASH
- * INTERNAL SPRING LOADED CHECK VALVES
- * SWIVELING SEAT DISKS
- * HOT SIDE STEM LEFT HAND
- * COLD SIDE STEM RIGHT HAND
- * STAINLESS STEEL SEATS
- * STAINLESS STEEL SEAT SCREWS
- * STAINLESS STEEL HANDLE SCREWS
- * 1/2" SLIP JOINT KIT INCLUDED

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 160°F MAX.
- * PRESSURE 200 PSI MAX. STATIC
- * 0.35 TO 2.20 GPM AT 80 PSI

SHIPPING WEIGHT

* 4.75 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com