

APPLICATION:		PRODUCT NAME: 8" ADJ. WALL MOUNT UTILITY SPRAY	
JOB NAME:		<input type="checkbox"/> SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL: <input type="checkbox"/> 2270 WITH WALL HOOK	
		OPTIONS OR MODIFICATIONS: <input type="checkbox"/> SUPPLY LINES (24" OR 36") CIRCLE LENGTH <input type="checkbox"/> ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH <input type="checkbox"/> BACKFLOW PREVENTER <input type="checkbox"/> PIPE HOOK <input type="checkbox"/> NIPPLES <input type="checkbox"/> ELBOWS <input type="checkbox"/> BRUSH <input type="checkbox"/> VANDAL RESISTANT KIT <input type="checkbox"/> HANDLES (CROSS OR WRIST) CIRCLE STYLE <input type="checkbox"/> OTHER _____	
		FEATURES: CONTROL VALVE * ECCENTRICS ADJUST FROM 7-3/4" TO 8-1/4" * INTERNAL SPRING LOADED CHECK VALVES * SWIVELING SEAT DISKS * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS SWIVEL ELBOW * 360° TURNING RADIUS HOSE * 60" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3 PLY FIBER REINFORCED INTERNAL RUBBER HOSE UTILITY SPRAY VALVE * NOZZLE THREADED INTO VALVE * 2.65 GPM AT 80 PSI * SHOWER SPRAY PATTERN * 45°F ANGLED HEAD SYSTEM LIMITS * TEMPERATURE: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT * 6.0 LBS	
ROUGH-IN: 		 FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com	