APPLICATION: PRODUCT NAME: STAINLESS STEEL PRE-RINSE 8" C/C BACKSPLASH MOUNT 3/4" FAUCET WITH 14" ADD-ON FAUCET SPECIAL CONFIGURATION JOB NAME: CHECK BASE MODEL AND OPTIONS QUANTITY: ITEM NO. MODEL: ☐ 24589 WITH WALL BRACKET FEATURES: 3/4" MAIN CONTROL VALVE * 8" C/C BACKSPLASH FAUCET * 3/4" NPT INLETS * SWIVELLING SEAT DISKS * HOT SIDE STEM - LEFT HAND * COLD SIDE STEM - RIGHT HAND * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS * CLOSE ELBOWS **BACKFLOW** WALL PREVENTER **BRACKET** 39 1/2" ADD-ON FAUCET [1003.3mm] * STEM - RIGHT HAND SWIVEL * COLD INDEX BUTTON 9 5/8" * FULL 3/4" SEAT OPENING [245.5mm] * SWIVELING SEAT DISKS * STAINLESS STEEL SEATS 14" * STAINLESS STEEL SEAT SCREWS [355.6mm] * STAINLES STEEL HANDLE SCREWS * 14" SPOUT WITH 1" DIAMETER OUTLET * FLOW RATE: 37.0 GPM AT 80 PSI HOSE * 36" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3-PLY FIBER REINFORCED INTERNAL **RUBBER HOSE ULTRA SPRAY VALVE** 8' **→** 4" → * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI [203.8mm] [101.4mm] * CLEANS FASTER - TEST PROVEN 3/4" NPT 12" (MAX) * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK **INLETS** [304.8mm] 2 3/4" * INTERCHANGEABLE - FITS ALL BRANDS [70.7mm] WALL BRACKET * ADJUSTS FROM 2" TO 12" SYSTEM LIMITS **ROUGH-IN** * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC SHIPPING WEIGHT * 18.0 LBS * NSF 61-9 APPROVED & LISTED www.truesdail.com [203.2mm] Ø1-1/4" [31.5mm] **ELBOWS** (INCLUDED) FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 EPAct 2005 Compliant ANSI/A112.18.1M information@fisher-mfg.com - www.fisher-mfg.com SPEC.

. 24589