

APPLICATION:		PRODUCT NAME: PRE-RINSE, SWIVEL STYLE, BACKSPLASH MOUNT	
JOB NAME:		<input type="checkbox"/> SPECIAL CONFIGURATION <input type="checkbox"/> CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL:	
		<input type="checkbox"/> 2611 ULTRA SPRAY VALVE NO WALL BRACKET <input type="checkbox"/> 2611-WB ULTRA SPRAY VALVE W/ WALL BRACKET	
		OPTIONS OR MODIFICATIONS: <input type="checkbox"/> SUPPLY LINES (24" OR 36") CIRCLE LENGTH <input type="checkbox"/> ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE <input type="checkbox"/> IN-LINE DUAL CHECK VALVE <input type="checkbox"/> PIPE HOOK <input type="checkbox"/> BRUSH <input type="checkbox"/> ELBOWS <input type="checkbox"/> HANDLES (CROSS OR WRIST) CIRCLE STYLE <input type="checkbox"/> VANDAL RESISTANT KIT <input type="checkbox"/> OTHER _____	
		FEATURES  <b>CONTROL VALVE</b> * 4" BACKSPLASH MOUNT * INTERNAL SPRING LOADED CHECK VALVES * HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS  <b>HOSE</b> * 15-1/2" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE  <b>ULTRA SPRAY VALVE</b> * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI * CLEANS FASTER - TEST PROVEN * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK * INTERCHANGEABLE - FITS ALL BRANDS	
		<b>SYSTEM LIMITS</b> * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC  <b>SHIPPING WEIGHT</b> * 12.0 LBS	
ROUGH-IN:  			
EPAct 2005 Compliant		ANSI/A112.18.1M	

# FISHER

FISHER MANUFACTURING COMPANY

TOLL FREE: 800-421-6162 - FAX: 800-832-8238

information@fisher-mfg.com - www.fisher-mfg.com