APPLICATION:		PRODUCT NAME:	
		PRE-RINSE SPRING STYLE SINGLE DECK WITH WALL BRACKET & ADD-ON FAUCET	
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL:	
		□ 34096 WITH 6" SWING SPOUT □ 34118 WITH 8" SWING SPOUT □ 34126 WITH 10" SWING SPOUT □ 34134 WITH 12" SWING SPOUT □ 34142 WITH 16" SWING SPOUT □ 34150 WITH 16" SWING SPOUT	
		OPTIONS OR MODIFICATIONS: □ SUPPLY LINES (24" OR 36") CIRCLE LENGTH	

Ī		THE PROPERTY OF THE PARTY OF TH	
38" [965.2mm]		П	
[965.2mm]			
		A	
	12" - [304.8m	_	
🛉			
"B"	_"C"	12" 04.8mm]	
"A"	3-3/4" [95.3mm] [50.8mm]	V	
[50.8m	🚡 🗼		
18.06j	5-3/5 [136.5] [136.5]	8" mml	
Ţ		nang	
1/2 SLIP JOIN			

ROUGH-IN	MODEL	DIM "A"	DIM "B"	DIM "C"
	34096	8-3/4" [221.3mm]	12-3/8" [313.3mm]	6" [152.4mm]
Ø7/8"	34118	9" [227.6mm]	12-7/8" [326.0mm]	8" [203.2mm]
[22.2mm]	34126	9-5/8" [243.5mm]	13-3/8" [340.3mm]	10" [254.0mm]
	34134	10-1/4" [259.4mm]	13-7/8" [351.4mm]	12" [304.8mm]
Ψ	34142	10-7/8" [275.2mm]	14-3/4" [373.7mm]	14" [355.6mm]
	34150	11-5/8" [294.3mm]	15-3/8" [389.5mm]	16" [406.4mm]

OTHER FEATURES:

☐ BRUSH

MAIN CONTROL VALVE

- * SINGLE DECK
- * STEM LEFT HAND SWIVEL

☐ IN-LINE DUAL CHECK VALVE

□ VANDAL RESISTANT KIT

- * HOT & COLD INDED BUTTONS
- * SWIVELLING SEAT DISKS
- * STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS

☐ ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE

☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE

TEMPERATURE CONTROL VALVE

- * INTERNAL CHECK VALVES
- * SCREWDRIVER ADJUSTMENT BOTH HOT & COLD

ADD-ON CONTROL VALVE

- * STEM RIGHT HAND SWIVEL
- * HOT INDEX BUTTON
- * SWIVELLING SEAT DISKS
- * STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS.

HOSE

- * 36" LENGTH
- * STAINLESS STEEL END FITTINGS
- * STAINLESS STEEL EXTERNAL JACKET
- * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
- * REPAIRABLE IN FIELD WITH SIMPLE TOOLS

ULTRA SPRAY VALVE

- * LOWEST ENERGY USER 1.15 GPM @ 60 PSI
- * CLEANS FASTER TEST PROVEN
- * ENGINEERED TO LAST NO 'O' RINGS TO LEAK
- * INTERCHANGEABLE FITS ALL BRANDS

WALL BRACKET

* ADJUSTS FROM 2" TO 12"

SYSTEM LIMITS

- * TEMP: 40°F MIN. TO 140°F MAX. STATIC
- * PRESSURE 200 PSI MAX. STATIC
- * SHIPPING WEIGHT: 14.0 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com