

APPLICATION:		PRODUCT NAME:  POT FILLER SVEI SWLH	
JOB NAME:		<input type="checkbox"/> SPECIAL CONFIGURATION <input type="checkbox"/> CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL: ■ 59552	
<p>Diagram labels and dimensions:</p> <ul style="list-style-type: none"> <li>WALL HOOK</li> <li>BACKFLOW PREVENTER</li> <li>2 3/8" [60.0mm]</li> <li>4-5/8" [117.5mm]</li> <li>2-1/2" [63.5mm]</li> <li>4 3/8" (MAX) [111.1mm]</li> <li>60" LENGTH HOSE</li> </ul>		OPTIONS OR MODIFICATIONS: <input type="checkbox"/> SUPPLY LINES (24" OR 36") CIRCLE LENGTH <input type="checkbox"/> ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH <input checked="" type="checkbox"/> BACKFLOW PREVENTER <input type="checkbox"/> PIPE HOOK <input type="checkbox"/> NIPPLES <input type="checkbox"/> ELBOWS <input type="checkbox"/> VANDAL RESISTANT KIT <input type="checkbox"/> HANDLES (CROSS OR WRIST) CIRCLE STYLE <input type="checkbox"/> OTHER _____	
		FEATURES:  <b>CONTROL VALVE</b> * SINGLE WALL MOUNT * STEM - RIGHT HAND * SWIVELING SEAT DISKS * HOT & COLD INDEX BUTTONS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS  <b>HOSE</b> * 60" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * BRAIDED USDA APPROVED FOODGRADE INTERNAL HOSE * REPAIRABLE IN FIELD WITH SIMPLE TOOLS  <b>POT FILLER VALVE</b> * NON SCRATCHING/ MARRING TUBE * 5.00 GPM AT 80 PSI * AERATED STREAM SWIVEL ELBOW * 360° TURNING RADIUS  <b>SYSTEM LIMITS</b> * TEMP: 40°F MIN. TO 160°F MAX. * PRESSURE 200 PSI MAX. STATIC  <b>SHIPPING WEIGHT</b> * 7.5 LBS	
ROUGH-IN:  <p>Diagram labels and dimensions:</p> <ul style="list-style-type: none"> <li>1/2" NPT FEMALE</li> <li>Ø7/8" [22.2mm]</li> </ul>		<p><b>FISHER</b>          FISHER MANUFACTURING COMPANY          TOLL FREE: 800-421-6162 - FAX: 800-832-8238          information@fisher-mfg.com - www.fisher-mfg.com</p>	
ANSI/A112.18.1M			