


Replacement Parts for Deck Mount Faucets



Stainless Steel 3/4" 8" Deck Mount Faucets Product Installation Guide

Since 1936, Fisher Manufacturing Company has manufactured heavy-duty, high quality plumbing products and hardware specialties for the food service industry. For three generations, the Fisher family has adhered to a strict dedication of overall value. When you install Fisher products... you install the best. Our hardware is manufactured with the standardization of internal mechanisms. Every piece of equipment we make is rigorously tested in both our modern in-house testing center and in actual field situations under extreme conditions. Every detail is thoroughly checked. Before we make our products available to you, they pass each and every test. You get proven performance. Guaranteed.



Limited One Year Warranty

Fisher Manufacturing Company warrants its products and parts thereof (except as noted below) against defects in materials or workmanship for a period of one year after the date of original purchase. During this period Fisher Manufacturing Company will replace a defective product or part without charge to you, provided that the entire product is delivered to Fisher Manufacturing Company. All transportation and insurance charges for shipping the product to and from Fisher Manufacturing Company must be borne by you. Charges for transportation and insurance may, at the option of Fisher Manufacturing Company, be refunded depending upon our investigation of the warranty claim. This warranty does not cover external finish (except at date of original purchase) or labor costs not specifically authorized by Fisher Manufacturing Company.

Lever Handles

- 77631 - 3/4" 8" Deck Mount Faucet 7" Swing Spout
- 60143 - 3/4" 8" Deck Mount Faucet 10" Swing Spout
- 51217 - 3/4" 8" Deck Mount Faucet 14" Swing Spout

Wrist Handles

- 77666 - 3/4" 8" Deck Mount Faucet 7" Swing Spout
- 60313 - 3/4" 8" Deck Mount Faucet 10" Swing Spout
- 51241 - 3/4" 8" Deck Mount Faucet 14" Swing Spout

A full and complete copy of our One Year limited warranty is available upon request.

WARNING:

Proposition 65 requires that we provide you with the following notice: "This product Contains A Chemical Known To The State Of California To Cause Birth Defects Or Other Reproductive Harm."



Installation Instructions for Deck Mount Faucets

BE SURE TO CHECK WITH YOUR LOCAL DEPARTMENT HAVING JURISDICTION REGARDING BACKFLOW PREVENTION

Installation Notes:

- Be sure to shut off water supply before beginning.
- Use pipe thread sealant such as PST on all threaded joints.
- Check the packaging for missing items BEFORE beginning installation. If items are missing, contact your supplier.

Tools Required for Installation


- Medium Sized Crescent Wrench
- Pipe Thread Sealant



Installation Instructions


1. Mount control valve on deck by inserting nipples through pre-drilled 1-3/4" holes in deck. Place washer and hex nut on nipples, tighten until control valve is secure. Apply thread sealant to both nipples and connect water supply
2. If installing a double joint spout, apply lube to the o-rings on the spout. Mount the double joint spout and tighten the nut onto the faucet spout outlet.
4. Apply lube to the o-rings on the swing spout. Make sure the white snap ring is in place before mounting the swing spout. Mount the swing spout and tighten the swing spout nut onto the faucet spout outlet.
5. Turn on water supply and check for leaks.

Step 1




Installation Instructions Continued

Step 2



Step 3



Step 4

