


PRODUCT NAME: STAINLESS STEEL  
SINGLE DECK PRE-RINSE WITH ADD-ON

- MODEL:
- 68012 6" SWING SPOUT W/ LEVER HANDLES
  - 68020 8" SWING SPOUT W/ LEVER HANDLES
  - 68039 10" SWING SPOUT W/ LEVER HANDLES
  - 68047 12" SWING SPOUT W/ LEVER HANDLES
  - 68055 14" SWING SPOUT W/ LEVER HANDLES
  - 68063 16" SWING SPOUT W/ LEVER HANDLES
  - 75930 6" SWING SPOUT W/ WRIST HANDLES
  - 75949 8" SWING SPOUT W/ WRIST HANDLES
  - 75957 10" SWING SPOUT W/ WRIST HANDLES
  - 75965 12" SWING SPOUT W/ WRIST HANDLES
  - 75973 14" SWING SPOUT W/ WRIST HANDLES
  - 75981 16" SWING SPOUT W/ WRIST HANDLES

- FEATURES:
- CONTROL VALVE**
- \* SINGLE DECK
  - \* STAINLESS STEEL CONSTRUCTION
  - \* SWIVEL SEAT DISK
  - \* STEM - LEFT HAND
  - \* LEVER HANDLES OR WRIST HANDLES
  - \* STAINLESS STEEL SWING SPOUT
- ADD-ON CONTROL VALVE**
- \* STEM - RIGHT HAND SWIVEL
  - \* HOT INDEX BUTTON
  - \* SWIVELLING SEAT DISKS
  - \* STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS.
- HOSE**
- \* 36" LENGTH
  - \* STAINLESS STEEL END FITTINGS
  - \* STAINLESS STEEL EXTERNAL JACKET
  - \* 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
  - \* REPAIRABLE IN FIELD WITH SIMPLE TOOLS
- ULTRA SPRAY VALVE**
- \* LOWEST ENERGY USER - 1.15 GPM @ 60 PSI
  - \* CLEANS FASTER - TEST PROVEN
  - \* ENGINEERED TO LAST - NO 'O' RINGS TO LEAK
  - \* INTERCHANGEABLE - FITS ALL BRANDS
- WALL BRACKET**
- \* ADJUSTS FROM 2" TO 12"
- SYSTEM LIMITS**
- \* TEMP: 40°F MIN. TO 140°F MAX. STATIC
  - \* PRESSURE 200 PSI MAX. STATIC
  - \* SHIPPING WEIGHT: 15.0 LBS
- \* NSF 61-9 APPROVED & LISTED  
[www.truesdail.com](http://www.truesdail.com)

FOOTPRINT:



ROUGH-IN:

