APPLICATION:					PRODUCT NAME:
					PRERINSE SPG 8BSLH
JOB NAME:					SPECIAL CONFIGURATION
QUANTITY: ITEM NO.				CHECK BASE MODEL AND OPTIONS	
22 7/8" [580.56]  WALL BRACKET  12" [304.8mm]  1-3/8" [34mm]  1/2" SLIP JOINT					SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS  MODEL: 73327 WITH 6" SWING SPOUT 73328 WITH 8" SWING SPOUT 73329 WITH 10" SWING SPOUT 73330 WITH 12" SWING SPOUT 73331 WITH 14" SWING SPOUT 73332 WITH 16" SWING SPOUT 73332 WITH 16" SWING SPOUT 73332 WITH 16" SWING SPOUT PTIONS OR MODIFICATIONS: SUPPLY LINES (24" OR 36") CIRCLE LENGTH HANDLES (CROSS OR WRIST) CIRCLE STYLE VANDAL RESISTANT KIT OTHER FEATURES  MAIN CONTROL VALVE 8" C/C BACKSPLASH MOUNT INTERNAL SPRING LOADED CHECK VALVES SWIVELLING SEAT DISKS HOT SIDE STEM - RIGHT HAND CHECK COLD SIDE STEM - RIGHT HAND CHECK STAINLESS STEEL SEATS, SEAT SCREWS, AND HANDLE SCREWS  HOSE 25 1/2" LENGTH STAINLESS STEEL END FITTINGS STAINLESS STEEL END FITTINGS STAINLESS STEEL EXTERNAL JACKET 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE REPAIRABLE IN-FIELD WITH SIMPLE TOOLS  ULTRA SPRAY VALVE LOWEST ENERGY USER - 1.15 GPM @ 60 PSI CLEANS FASTER - TEST PROVEN ENGINEERED TO LAST - NO 'O' RINGS TO LEAK INTERCHANGEABLE - FITS ALL BRANDS
					WAL BRACKET * ADJUSTS FROM 2" TO 12"
ROUGH-IN	MODEL	DIM "A"	DIM "B"	DIM "C"	
Ø7/8"	73327	8-3/4" [221mm]	12-3/8" [313mm]	6" [152mm]	* TEMP: 40°F MIN. TO 160°F MAX.
[22mm]	73328	9" [228mm]	12-7/8" [326mm]	8" [203mm]	* PRESSURE: 200 PSI MAX. STATIC
	73329	9-5/8" [244mm]	13-3/8''' [340mm]	10" [254mm]	* 15.0 LBS
	73330	10-1/4" [259mm]	13-7/8" [351mm]	12" [305mm]	
8" [203mm]	73331	10-5/8" [275mm]	14-3/4" [374mm]	14" [356mm]	



73332



11-1/2" [292mm]



15-3/8" [390mm]

16"

[406mm]

FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com