APPLICATION:		PRODUCT NAME:
		PRE-RINSE 8" ADJ. WALL MOUNT
		3/4" FAUCET WITH 14" ADD-ON FAUCET
JOB NAME:		SPECIAL CONFIGURATION
QUANTITY:	ITEM NO.	CHECK BASE MODEL AND OPTIONS
		MODEL:
WALL BRACKET 39 1/2" [1003.3mm] 17" [431.5mm] 14" [355.6mm] [218.2mm]		□ 84840 WITH WALL BRACKETS
		FEATURES:
		3/4" MAIN CONTROL VALVE * 8" ADJ. WALL CONTROL FAUCET
		* 3/4" FEMALE NPT INLETS
		* SWIVELLING SEAT DISKS
		* HOT SIDE STEM - LEFT HAND
		* COLD SIDE STEM - RIGHT HAND
		* STAINLESS STEEL SEATS
		* STAINLESS STEEL SEAT SCREWS
		* STAINLESS STEEL HANDLE SCREWS
		ADD-ON FAUCET
		* STEM - RIGHT HAND SWIVEL
		* COLD INDEX BUTTON
		* FULL 3/4" SEAT OPENING
		* SWIVELING SEAT DISKS
		* STAINLESS STEEL SEATS
		* STAINLESS STEEL SEAT SCREWS * STAINLES STEEL HANDLE SCREWS
		* 14" SPOUT WITH 1" DIAMETER OUTLET
		* FLOW RATE: 37.0 GPM AT 80 PSI
		HOSE
		* 36" LENGTH
		* STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET
		* 3-PLY FIBER REINFORCED INTERNAL
		RUBBER HOSE
-7-1/2"-8-1/2"- [124 0mm]		
- -7-1/2"- -		ULTRA SPRAY VALVE
12" (MAX) ——— 2 1/8"——		* LOWEST ENERGY USER - 1.15 GPM @ 60 PSI * CLEANS FASTER - TEST PROVEN
[304.8mm] [53.3mm]		* ENGINEERED TO LAST - NO 'O' RINGS TO LEAK
		* INTERCHANGEABLE - FITS ALL BRANDS
3 1/2"		WALL BRACKET
ROUGH-IN	[89.0mm]	* ADJUSTS FROM 2" TO 12"
		SYSTEM LIMITS
		* TEMP: 40°F MIN. TO 140°F MAX.
		* PRESSURE 200 PSI MAX. STATIC
		SHIPPING WEIGHT * 18.0 LBS
A REPORT OF THE PARTY OF THE PA		10.0 LD3
Ø1-1/4"		
[31.8mm] 7-1/2"-8-1/2" [190.5mm-215.9mm]		
		HISHER
		FISHER MANUFACTURING COMPANY
EPAct 2005 Compliant	(F) ANSI/A112.18.1M	TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com
•	·	